

# Hot Water Flowmeters


ManuFlo has enhanced its Hot Water flowmeter product range, introducing the **SW-H** type turbine flowmeters that operate to 130°C, are available in sizes from 50-200mm, and also have optional pulse output.

On Hot Water flowmeters, the optional pulse output is useful for batching applications as well as remote or resettable totalising.

Usually, the pulse output option is ordered at the time the meter is purchased, but with the SW-H flowmeter (shown at right), pulse output capability can easily be retrofitted to existing units.

## SW-H

- to 130 °C (without pulse output).
- accuracy:  $\pm 2\%$ .
- sizes 50-200mm.
- running (non-resettable) totaliser.
- with optional pulse output:
  - to 110 °C
  - sizes 50- 80 mm: 1 pulse/ 10L
  - sizes 100-200 mm: 1 pulse/ 100L



## RPFS-H

- to 120 °C.
- accuracy:  $\pm 2.5\%$ .
- transistor pulse output. 5-30 VDC powered.
- with 2-metre lead, and lockcap.
- with various adapters for 20-500mm pipes.

## RPFS-L

- to 120 °C.
- Inductive coil pulse output for use with battery powered Indicators.



## ETDA

- to 120 °C.
- size: 20mm.
- Flowrange @  $\pm 2\%$  accuracy: 3.3 – 83.3 Litres/min.
- running (non-resettable) totaliser.
- with optional Reed Switch pulse output: 1 pulse / 1 Litre.

## CT5-S15

- to 90 °C.
- size: 15mm.
- flowrange @  $\pm 1.5\%$  accuracy: 0.25 - 40 Litres/min.
- with optional Reed Switch pulse output: 120 pulses/Litre.



## ME4

- to 90 °C.
- size: 15mm.
- Flowrange @  $\pm 2\%$  accuracy: 0.5 – 50 Litres/min.
- running (non-resettable) totaliser.
- with optional Reed Switch pulse output: 1 pulse / 1 Litre.



Also available: PMS electromagnetic flowmeters, to 130 °C, sizes 3 - 250mm.

**ManuFlo** <sup>®</sup>TM

**Flow Measurement & Control Products**

a division of

**MANU ELECTRONICS PTY LTD**

Rev: 1109/1

41 Carter Road, Brookvale  
Sydney NSW 2100 Australia  
Ph: + 61 2 9905-4324, 9938-1425  
Fax: + 61 2 9938-5852

**Web: [www.manuelectronics.com.au](http://www.manuelectronics.com.au)**  
**Email: [sales@manuelectronics.com.au](mailto:sales@manuelectronics.com.au)**