

K600 - flowmeters for oil, petrol, diesel and kerosene

- Oval gear positive-displacement inline flowmeters for oil, petrol, diesel and kerosene.
- High precision.
- Low pressure losses.
- Compact lightweight design.
- Easy installation and use.
- Aligned inlet/outlet apertures.
- Independent battery powered.



K600/4

| | K600/2 | K600/3 | K600/4 |
|--------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| connections | ¾" BSP (female) | 1" BSP (female) | 1 ½" BSP (female) |
| LCD display | • Flowrate • Resetable total | • Flowrate • Resetable total | • Flowrate • Resetable total |
| Flowrange (Litres/min) | 6 - 60 | 10 - 100 | 15 150 |
| Accuracy | ± 0.5% | ± 0.5% | ± 0.5% |
| Repeatability | ± 0.2% | ± 0.2% | ± 0.2% |
| Max. pressure | 7000 kPa | 3000 kPa | 2000 kPa |
| Max. temp | 50 °C | 50 °C | 50 °C |
| Max. Pressure loss | < 0.5 bar (7psi) | < 0.5 bar (7psi) | < 0.5 bar (7psi) |
| Power | 2x AAA 1.5v alkaline batteries | 2x AAA 1.5v alkaline batteries | 2x AAA 1.5v alkaline batteries |
| Measuring chamber | Aluminium | Aluminium | Aluminium |
| Oval gears | Acetalic resin | Acetalic resin | Acetalic resin |
| Package (mm) | 200 x 120 x 140 | 200 x 120 x 140 | 200 x 120 x 140 |
| Weight | 2 kg | 2.6 kg | 3.2 kg |
| Compatible Liquids: | | | |
| Lubricating & Transmission Oil | Yes | No | No |
| Rapsoil | Yes | No | No |
| Diesel fuel | No | Yes | Yes |
| Antifreeze | Yes | Yes | Yes |
| <p>K 600/3</p> | | | |