

Mechanical Totaliser Flowmeters

Non-resettable.

Also available with pulse output in addition to totaliser.



MESM series

- Sizes: 20, 25, 32, 40 & 50 mm.
- Shows total m³ (KL) in 1 Litre units.
- Series flowrange @ $\pm 1.5\%$ accuracy: 1.5 - 600 Litres/min.
- Nutating disc measuring chamber.
- $\frac{3}{4}$ " BSP (male) connection ends.



MEH series

- Sizes: 15 - 300 mm.
- Shows total m³ (KL) in 0.1 Litre units.
- Series flowrange @ $\pm 2.5\%$ accuracy: 2 - 25000 Litres/min.
- 15 - 50 mm: BSP (male) connection ends.
- 80 - 300 mm: Table E flanged.



SW series

- ideal for water distribution networks.
- Sizes: 50-200 mm.
- Shows total m³ (KL) in 1 Litre units
- Series flowrange @ $\pm 2\%$ accuracy: 16 - 13300 Litres/min.
- ANSI flanged (50 & 80mm also available in Table D Flanged).



SIM series

- for irrigation water applications (raw water, water containing solid particles).
- Sizes: 65-200 mm.
- Shows total m³ (KL) in 5 Litre units (0.5 Litre units for 65mm size).
- Series flowrange @ $\pm 5\%$ accuracy: 13 - 8333 Litres/min.
- Proportional measurement type.
- Table D Flanged.



PSM series

- for cold potable water measurement.
- Sizes: 15, 20, 25, 32 & 40 mm.
- Shows total in 1 Litre units.
- Series flowrange @ $\pm 2\%$ accuracy: 0.5 - 250 Litres/min.
- 15-25 mm: Gasket-Seat/Ball-Seat couplings.
- 32-40 mm: Flanged.



ME4

- hot water flowmeter, to 90 °C.
- Size: 15 mm.
- Shows total m³ (KL) in 1 Litre units
- Flowrange @ $\pm 2\%$ accuracy: 0.5 - 50 Litres/min.
- Single-jet turbine type.

ManuFlo®™

Flow Measurement & Control Products

a division of

MANU ELECTRONICS PTY LTD

Rev: 0903/1

41 Carter Road, Brookvale
Sydney NSW 2100 Australia
Ph: + 61 2 9905-4324, 9938-1425
Fax: + 61 2 9938-5852

Web: www.manuelectronics.com.au
Email: sales@manuelectronics.com.au

See all our datasheets at http://www.manuelectronics.com.au/data_sheets.html