

Resettable Flowmeters



MESLCD series

- Ideal for batching applications.
- 4 or 5-digit LCD shows total Litres.
- Closing lid resets Litres count.
- Sizes: 20-50mm
- Series flowrange: 1.5 - 600 Litres/min.
- Nutating disc measuring chamber.
- Internal Lithium battery powered.



MRPU5 series

- Ideal for batching applications.
- 5-digit LCD shows total Litres.
- Closing lid resets Litres count.
- Sizes: 25-200mm
- Series flowrange: 18 - 15070 Litres/min.
- Paddlewheel type. Various pipe adapters.
- Internal Lithium battery powered.

Integral resettable display

ME5-T-B resettable Totaliser Indicator

- LCD shows **resettable Total**.
- Programmable.
- internal Lithium battery (5 - 10 year battery life).
- IP65 enclosure.



FRT303-B Indicator

- LCD shows **Flowrate, Total (resettable) and Grand Total**.
- Programmable.
- internal Lithium battery (5 - 10 year battery life).
- IP65 enclosure.



ME7 resettable Indicator

- 8-digit **resettable totaliser**.
- 1 input pulse = 1 count (no scaling).



Combinations with remote resettable display

RPFS-L

- paddlewheel flow sensor.
- **inductive coil pulse output**.
- with various adapters for 20-500mm pipes.
- **for fresh or mild recycled water.**



MEHR multi-jet series

- **running (non-resettable) mechanical total and with Reed Switch Pulse output.**
- in sizes 15-50 mm.
- power not required.
- **ideal for low pressure applications.**



MEHR turbine series

- **running (non-resettable) mechanical total and with Reed Switch Pulse output**
- 1 pulse/100L ≤100mm or 1 pulse/KL >100mm.
- sizes 80-200 mm.
- Power not required.



ManuFlo®™
Flow Measurement & Control Products

a division of

MANU ELECTRONICS PTY LTD

Rev: 1111/1

41 Carter Road, Brookvale
Sydney NSW 2100 Australia
Ph: + 61 2 9905-4324, 9938-1425
Fax: + 61 2 9938-5852

Web: www.manuelectronics.com.au
Email: sales@manuelectronics.com.au