


Tradewaste Flowmeters


Compliant to Sydney Water requirements

You need to **tell us your:**

- pipe diameter e.g. 50mm;
- pipe type e.g. PVC, Galvanised Iron;
- liquid being measured;
- approx. min & max flowrate in Litres/min;
- approx. discharge volume in Litres/day.
- flowmeter installer.



Flowmeter is delivered ready to install:

- ☺ With Sydney Water special tradewaste sampler plugs fitted. 
- ☺ Fully programmed to Sydney Water specifications.
- ☺ Sensor Wired to Display, which has a boundless totaliser.
- ☺ With Flanged Connection Kit (if requested).
- ☺ Tested (calibration certificate supplied).
- ☺ Automatically self-verifies, for the ultimate in operational stability and repeatability.

Additional Service

ManuFlo on-site flowmeter verification service.



For pipe sizes:
25, 40, 50, 80, 100, 150 & 200mm
with optional PVC or GAL
connection kits (up to 150mm size)
for easy plumbing install.

Technical details

- **Pipe sensor:** Obstructionless bore (virtually maintenance free).
- **Display:** includes Total and Flowrate.
- **Connection:**
 - 40 & 50mm: AS2129 Table F flanged
 - all other sizes: AS4087 flanged, Class 16
- **Power:** 85 - 253vac
- **Cable:** 2-metre power lead

ManuFlo®™

Flow Measurement & Control Products

- Sydney-based company, founded in 1965.
- One of the founding companies in tradewaste measurement (1984).

41 Carter Road, Brookvale
Sydney NSW 2100 Australia
Ph: + 61 2 9905-4324, 9938-1425
Fax: + 61 2 9938-5852

Web: www.manuelectronics.com.au
Email: sales@manuelectronics.com.au