radewast

Compliant to Water Corporation requirements

You need to tell us your:

- pipe diameter e.g. 50mm;
- pipe type e.g. PVC, Galvanised Iron;
- liquid being measured;
- approx. min & max flowrate in Litres/min;
- approx. discharge volume in Litres/day.





For pipe sizes: 25, 40, 50, 80, 100, 150 & 200mm with optional PVC or GAL connection kits (up to 150mm size) for easy plumbing install.

We customise the flowmeter for your application

Flowmeter is delivered ready to install:

With Water Corporation special tradewaste sampler plug fitted.



- Fully programmed to Water Corporation specifications.
- Sensor Wired to Display, which has a boundless totaliser.
- With Flanged Connection Kit (if requested).
- Tested (calibration certificate supplied).
- Automatically self-calibrates, for the ultimate in operational stability and repeatability.

Additional Service

Verimaster on-site flowmeter verification service.

Technical details

- Pipe sensor: Obstructionless bore (virtually maintenance free).
- Display: includes Total and Flowrate.
- Connection:
 - 40 & 50mm: AS2129 Table F flanged.
 - all other sizes: AS4087 flanged, Class 16.
- Power: 85 265vac
- Cable: 2-metre power lead



Flow Measurement & Control Products

- Sydney-based company, founded in 1965.
- One of the founding companies in tradewaste measurement (1984).

41 Carter Road, Brookvale Sydney NSW 2100 Australia

Ph: +61 2 9905-4324, 9938-1425

Fax: +61 2 9938-5852

Web: www.manuelectronics.com.au Email: sales@manuelectronics.com.au

